

Testing Report

Test Items		Methods of Testing	Colour No.	1	2	3	4	5	6
Colour Fastness	Ultraviolet carbon arc lamp light (Grade)	JIS L 0842	change in colour						
	Washing and Laundering (Grade)	JIS L 0844	change in colour						
		Method A-2	staining						
	Perspiration (Grade)	JIS L 0848	acid						
			alkali						
	Rubbing (Grade)	JIS L 0849	dry						
		Type II	wet						
	Water (Grade)	JIS L 0846	change in colour						
Dimensional Change	Dry cleaning (Grade)	JIS L 0860	change in colour						
		Method A-1	staining						
	Light and Perspiration (Grade)	JIS L 0888	acid						
		Method B	alkali						
	Water Drop (Grade)	JIS L 0853	change in colour						
Strength	Determination of formaldehyde JIS L 1041 Method B(ppm)								
	Steep Method (%)	JIS L 1096	warp						
		Method C	weft						
	Pressing Method (%)	JIS L 1096	warp						
		Method H-2	weft						
	Dry cleaning Method (%)	JIS L 1096	warp						
Strength	Electric washing machine Method (%)	Method J-1 Tumbler drying	weft						
		JIS L 1930	warp						
	Electric washing machine Method (%)	No.C4G screen drying	weft						
		JIS L 1930	warp						
		No.C4H screen drying	weft						
	Pilling (Grade)	JIS L 1076	3hour	2.5					
		Method A	5hour	(2.0)					
	Tearing Strength (N)	JIS L 1096	warp						
		Method D	weft						
Strength	Water absorbency of textiles (second)	1907	initial						
		Dripping method	after						
	Water vapour permeability of textiles (g/m ² ·h)	JIS L 1099							
		Method A-1							
Strength	Cool touch feeling property (W/cm ²)	JIS L 1927							

Applicant	MONTELUCE／MARUYASU Corporation	
	Okubo	
Article	1/50 CLAIR SILK	
	1 Piece	
polyester 85%		
silk 15%		

Laboratory	THE JAPAN COTTON & STAPLE FIBER FABRIC INSPECTING INSTITUTE FOUNDATION	
	1-10-5, Komagome, Toshima-ku, Tokyo, Japan	
	TEL 03-3943-3174	
	FAX 03-3943-3183	
	Date	2025/9/4
	Test No.	TO-2607417-2
InspectionHouse	Tokyo Test Center	
	Inspector <i>S. Sato</i>	
Adjacent Fabric		Cotton / Nylon (multifiber fabric)

SAMPLE	1 OFFWHITE	2	3	4	5	6
	WANKEN MENKEN					

Quantitative analysis of fibre mixtures (%)	
JIS L 1030-2	